


## Item description/product images



## Description

**Material:**

GJL 300.

**Version:**

Support and mounting surfaces ground

**Note:**

Baseplates with T-slots are used for constructing modular fixtures. These baseplates are positioned and mounted directly on machine tables.

The precise longitudinal and transverse slot spacing ensures very high repeat clamping accuracy.

The two locating holes are used to align the baseplate on the machine table.

Fastening holes are produced by the customer to suit their machine table.

Please order locating pins to locate the baseplates separately.


Ring bolts with T-nuts for hoisting are supplied.

Other dimensions available on request.

**Drawing reference:**

1) locating hole

## Drawings



## Overview of items

Order No.	L	B	H	H4	D2	L6	L9	BN=Slot width	NL=No. lengthwise	NB= No. across
01126-31440060	600	400	60	23	30	500	100	14	5	3
01126-31450060	600	500	60	23	30	500	100	14	5	4
01126-31460060	600	600	60	23	30	500	100	14	5	5
01126-31440080	800	400	60	23	30	700	100	14	7	3
01126-31445090	900	450	60	23	30	800	100	14	8	3
01126-31450100	1000	500	60	23	30	900	100	14	9	4
01126-31460120	1200	600	60	23	30	1100	100	14	11	5
01126-31840060	600	400	75	30	30	500	100	18	5	3
01126-31850060	600	500	75	30	30	500	100	18	5	4
01126-31860060	600	600	75	30	30	500	100	18	5	5
01126-31840080	800	400	75	30	30	700	100	18	7	3
01126-31845090	900	450	75	30	30	800	100	18	8	3
01126-31850100	1000	500	75	30	30	900	100	18	9	4
01126-31860120	1200	600	75	30	30	1100	100	18	11	5